FARRELL ANCHORING CEMENT
PRODUCT DATA SHEET

Quick Setting & Non-Shrinking Anchoring Cement

DESCRIPTION
Farrell Anchoring Cement is a one-component, waterproof, nonshrinking, Portland Cement-based anchoring cement that sets hard in 12-15 minutes. It expands as it sets and locks into the surrounding concrete.

USES
Anchors bolts, lamp posts, signs, hand railings, fence, and mail box posts, etc. Can be used both interior and exterior.

ADVANTAGES
1. Quick-setting
2. Non-shrinking
3. Rock hard
4. Self-locking
5. Stronger than concrete
6. Easy to use

TECHNICAL DATA
Compression: 4700 P.S.I.

PACKAGING: 50 lb. plastic pail

INSTALLATION
MIXING
Mix only enough material to apply in 8 minutes and to fill the hole. Mix with clean water approx. 16.7% by weight or 1 gallon per 50# to a uniform, lump-free pancake batter consistency in a small plastic bowl or other suitable container. Do not over-water the material.

Anchoring In Vertical Surfaces (Putty Consistency):
Fill hole with putty-like cement first. Then temp bolt or rod into place. Let stand a few minutes before smoothing out the surface with a putty knife. Let harden for 30 minutes; then sprinkle with water. For best results, allow anchor to sit overnight before weight is applied.

Anchoring in Horizontal Surfaces (Pourable Consistency):
Drill or chisel hole in concrete, brick, or stone at least 3" deep. Hole should not be tapered. Blow out all dust and loose material and flood hole with water. Scrub side and bottom with stiff brush, and remove excess water. Provide washers on anchor bolts before placing in hole. Place bolt in hole and fill with Anchoring Cement. Be sure to taper Anchoring Cement up and around bolt or rod about ¼" above surface to avoid a trap where water and dirt may accumulate.

NOTE
Anchoring Cement may weaken and erode if continuously exposed to running or still water. Where these conditions exist, the product should be tapered and coated with a good quality concrete sealer or waterproof paint. Anchor Cement is a hole filler only, not a surface patch, because it expands when setting.

WARRANTY
This product is manufactured with high-quality raw materials in strict compliance with Farrell Equipment & Supply's specifications. Farrell guarantees the purchase price of the product or will provide a replacement when applied according to manufacturer's instructions. Improper mixing and application, along with environmental factors beyond Farrell's control, voids this warranty. All warranty claims are up to Farrell's discretion.

MADE IN USA

FARRELL EQUIPMENT & SUPPLY CO.

EAU CLAIRE
715-835-4334
Fax: 715-835-4356
1510 N Hastings Way
Eau Claire, WI 54703

APPLETON
920-903-1985
Fax: 920-903-8278
3920 E Endeavor Drive
Appleton, WI 54915

LA CROSSE
608-796-9300
Fax: 608-796-9435
508 Monitor Street
La Crosse, WI 54603

MADISON
608-222-5372
Fax: 608-222-5405
6809 Mangrove Lane
Monona, WI 53713

ROCHESTER
507-252-0234
Fax: 507-252-0222
1635 3rd Avenue SE
Rochester, MN 55904

ST. PAUL
651-756-8932
Fax: 651-756-8864
2310 Ventura Drive
Woodbury, MN 55125

WAUSAU
715-355-8300
Fax: 715-298-1662
7405 Commerce Drive
Weston, WI 54476

© Farrell Equipment & Supply Co., Inc. • 2019 Version 1.0